

CU-3E19RBU-5 MULTI-ZONE SYSTEM

-5°F Heat Operation

2-3

Zone (1.5 Ton)

CU-3E19RBU-5

Cooling Capacity: 19,000 (6,100 - 24,800) Btu/hr
 Heating Capacity: 26,000 (5,000 - 28,400) Btu/hr
 SEER Non-Ducted 22.0 / Ducted 18.5
 EER Non-Ducted 12.55 / Ducted 10.85
 HSPF Non-Ducted 10.5 / Ducted 9.0
 Min/Max capacity 15,300 - 30,600 Btu/hr



Wireless Controller (Included)



Wired Remote Controller CZ-RD516C-1 (Optional)



Wireless App Control

Connect 2 to 3 Indoor Units



CS-ME5RKUA / CS-ME7RKUA / CS-E9RKUAW / CS-E12RKUAW / CS-E18RKUAW



CS-XE9WKUAW / CS-XE12WKUAW / CS-XE15WKUAW / CS-XE18WKUAW



(Non-Ducted)

CU-3E19RBU-5



Wireless Controller (Included)



Wired Controller with 32 ft cable CZ-RD52CU (Optional)



CZ-BT20U



All multi-split condensers must have minimum two indoor units installed.

Outdoor Unit

| MODEL NO. | | CU-3E19RBU-5 | |
|---|-----------------------|---|-----------------------|
| Performance | | Cooling | Heating |
| Capacity | Btu/h | 19,000 (6,100-24,800) | 26,000 (5,500-28,400) |
| Air Circulation | High CFM | 1,447 | 1,634 |
| Number of Connectable Indoor Units | | 2-3 | |
| SEER | Non-Ducted / Ducted | 22.0 / 18.5 | |
| EER | Non-Ducted / Ducted | 12.55 / 10.85 | |
| HSPF | Non-Ducted / Ducted | 10.5 / 9.0 | |
| Electrical Rating | | | |
| Power Supply | V, Phase, Hz | 230V / 208V, 1PH, 60Hz | |
| Running Ampere | Non-Ducted / Ducted A | 7.4-6.7 / 8.5-7.7 | 10.1-9.1 / 12.3-11.1 |
| Power Input | W | 1,510 (360-2,420) | 2,060 (320-2,300) |
| Maximum Fuse Size : MCA / MOCP | Amps | 20/30 | |
| Features | | | |
| Controls | | Microprocessor | |
| Fan Speeds | | Variable Speed | |
| Compressor | | Twin Rotary, DC Motor, Inverter | |
| Refrigerant / Amount Charged at Shipment | | R-410A / 93.2 oz | |
| Refrigerant Control | | Electronic Expansion Valve | |
| Operation Sound | Hi dB-A | 50 | 52 |
| Refrigerant Tubing Connections | Type | Flare | |
| Max. Allowable Tubing Length | Ft. | 164 per system (82 per indoor unit) | |
| Refrigerant Tube Diameter (service value) | Discharge inch | 1/4" x 3 | |
| | Suction inch | 3/8" x 3 | |
| Adapter Required | | Indoor 12 and 18 Btu/hr. require 1 CZ-MA1P-US | |
| Dimensions & Weight | | | |
| Unit Dimensions | H x W x D inch | 31-5/16 x 34-15/32 x 14-3/6 | |
| Net Weight | Lbs. | 159 | |

Important: You must use refrigerant piping rated for R410a.